

Easytrak Nexus 2 USBL System, Model EZT-2691



Key features

- Bi-directional Sigma 2 Spread Spectrum acoustics
- Improved positioning accuracy and stability
- Multi Fire optimised beacon refresh rate
- MIL Specification EMC
- MIL Specification Environmental
- 16 target tracking
- Geographical navigation overlays
- EasyCal 2 embedded calibration tool with AutoCal Wizard
- Data telemetry options

Easytrak Nexus 2 Overview

Easytrak Nexus 2 is the next generation of advanced USBL positioning and tracking system that incorporates Sigma 2 Spread Spectrum technology to provide a secure acoustic link. By incorporating AAE Sigma 2 technology the wide bandwidth transmissions reduce its susceptibility to interference and enables precise, reliable positioning over an extended operational range.

The MIL grade Easytrak Nexus 2 determines the position of dynamic subsea targets through the transmission and reception of acoustic signals between the submerged transceiver and the target beacon. Positions can be geographically referenced with chart overlays and internally logged for a complete solution.

Nexus 2 Technical Specification

Code: EZT-2691 is under U.K. Export Control ML9a1

EASYTRAK NEXUS CONSOLE, CODE: EZT-2691-3U/KRN

Dimensions	19" Rack mount. 3U 446 x 132.5 x 434.5mm
Weight	5.4kg
Mounting	Chamberlain D466VD-450 Slide
Power requirements	210 – 240 VACRMS. 2ARMS, (Following boot.) 7A Max Peak to Peak Inrush upon transceiver initialisation. Power on system boot.
Connection to Transceiver	Rear-panel connector for EZT-2686 Transceiver
Built-in PC	Intel I5 running embedded Windows 7. Solid state hard disk
Front panel indicators	LED indicators for power and serial status
Serial communications	5 x RS-232. Selectable Baud rates
Data Output	AAE format V1 and V2, TP-II2EC, TP-EC W/PR, Simrad 300P, Simrad 309, Simrad \$PSIMSSB, Pseudo \$GPRMC, NMEA \$GPGGA, NMEA \$GPVTG, NMEA \$GPTLL,Pseudo \$GPGGA, KLEIN 3000 (Quick set) Multiple outputs available
Compass Input	TCM-2.X, SGB-HTDS, SGB-HTDt, \$HEHDT, \$HDHDM, \$HDHDT, \$HDHDG
VRU Input	TCM-2.X, \$HCXDR , TSSI
GPS / DGPS Input	NMEA; GLL, GGA, RMC
Target Heading Input	NMEA HDM, HDT, HDG, PNI TCM2
Target Depth Input	NMEA DBT, DBK, DBS, DPT, AAE
Time in	GPS Time synch
Responder Output	Pulse: Positive 12V pulse 5ms long
USB	3 ports available
Ethernet	Rear panel standard RJ45 jack
Audio	Audible activity indicator

Nexus 2 Technical Specification

Factory calibrated multi-element transceiver head complete with integral AHRS, depth sensor and temperature sensor.

TRANSCEIVER, TYPE EZT-2686-KRN and EZT-2780-KRN SPECIFICATIONS

Material	Stainless steel
Weight in air/water	2686: 16kg/11kg 2780: 21kg/15kg
Dimensions	2686: 152mm Ø x 432mm 2780: 200mm Ø x 432mm
Temperature	Operating: -10° to +40°C Storage: -20° to +50°C
Depth rating	30m
Electrical supply	48Vdc
Depth sensor (Pressure Sensor)	5 bar, accuracy 0.25% between -10° to +40° C
Temperature sensor	1° resolution between -10° and +40° C
Frequency band (MF)	18 - 32 kHz
Tracking beam pattern	2686: 180° 2780: 150°
Transmitter	Variable, typical max 192dB re 1µPa at 1m
Compatible transponders	AAE Sigma 1, Sigma 2 Digital Spread Spectrum and AAE Tone channels. AAE V-NAV channels. HPR 400 channels 1100, 1000, 1200A, 1300A Series Beacons, Digital Depth Transponders, AAE Release and Telemetry Beacons.
Interrogation rate	>2Hz refresh rate. Internally set or external key
System	Externally assessed for immunity and emissions; conforms to 89/336/EEC. RoHS compliant
Cable length	Max 150m

Tranceiver Performance

Accuracy is based on the correct speed of sound being entered, no ray bending and an acceptable S/N ratio

Position repeatability, calibrated and measured with SNR > 20dB rel.1μPa in a controlled test environment

Tranceiver	Console	Beam Pattern	Acoustic precision degrees	Acoustic % slant range	Internal AHRS precision	Acoustic + internal AHRS %	Acoustic + external AHRS %	Max range	Range resolution	UK Export control
EZT-2686-N	EZT-2692	180°	0.25° DRMS	0.45%	0.5°	1.49%	0.45%	995m	0.01m	No
EZT-2686-C	EZT-2692	180°	0.25° DRMS	0.45%	0.5°	1.49%	0.45%	2000m	0.01m	Yes
EZT-2780-N	EZT-2692	150°	0.07° DRMS	0.12%	0.5°	1.17%	0.45%	995m	0.01m	No
EZT-2780-C	EZT-2692	150°	0.07° DRMS	0.12%	0.5°	1.17%	0.45%	2000m	0.01m	Yes

TRANSCIEVER CABLE, CODE: EZT-MC-50/KRN

Code: EZT-MC-50 is under U.K. Export Control ML9a1

Diameter	12.8 mm nominal
Colour	Yellow
Length	50 metre standard length
Connectors	Supplied
SWL	20 kg. Allows transducer to be deployed from cable

ELECTRO MAGNETIC IMMUNITY (EMI)

MIL STD 461D tests	CE101, CE102, RE101, RE102, CS101, CS114, RS101, RS103 to an upper limit of 1GHZ
---------------------------	--

ENVIRONMENTAL SPECIFICATION

High Temp Test (MIL-STD-810F. METHOD 501.4)	Storage: 43°C Operational: 30°C
Low Temp Test (MIL-STD-810F. METHOD 502.4)	Storage: -20°C Operational: 0°C
Humidity Test (MIL-STD-810F. METHOD 507.4)	

VIBRATION DEF STAN 00-35 Part 3: Issue 4

M1: General Purpose Vibration Test: Deployed or installed in surface ships: Sine sweep

M1: General Purpose Vibration Test: Deployed or installed in surface ships: Sine dwell

Test Type	Region	Amplitude (mm pk)	Frequency (Hz)	Duration (mins)
Sine Sweep	Upper deck, Protected Compartment and Hull	0.125	5 to 33	60
Sine Dwell	All	1.250	14	20
		0.300	23	20
		0.125	33	20

SHOCK DEF STAN 00-35 Part 3: Issue 4

M7: Shock Testing for Warship Equipment & Armament Stores: Classical Shock Pulse

NCUE – Classical Shock Pulse

	Vertical	Lateral	Longitudinal
Pulse Shape	Half Sine		
Pulse Width	10ms		
Acceleration	45g	25g	25g
Duration	1 shock in each direction of each orientation (6 in total)		

See operational specification for testing methodology.