



# SWiFTplus Phycocyanin

## Multi-parameter profiler

Cyanobacteria (or blue-green algae) are photosynthetic bacteria that occur naturally in surface waters. Under certain conditions of light, temperature and nutrient levels cyanobacteria can multiply rapidly, forming a bloom. Some Cyanobacteria produce toxins which pose health risks for humans and animals. The EU Bathing Waters Directive therefore requires monitoring for these blue-green algae blooms.

Testing for the actual toxins is possible by means of laboratory analysis of water samples, but this can be costly and time-consuming. However, cyanobacteria contain a fluorescent pigment called Phycocyanin, which can be detected in real time using a Valeport Hyperion fluorometer. The Hyperion uses narrow bandpass filters on both excitation and emission wavelengths to ensure that the response is specific to Phycocyanin and not affected by false positive results from normal Chlorophyll a fluorescence.

## DATA SHEET

### Product Details



MULTI-PARAMETER CTD



SOUND SPEED



OPTICAL



CONNECT SOFTWARE



Bluetooth



USB



Rechargeable  
Battery



GPS

TAE KWANG ELECTRONICS CORPORATION  
5TH FLR., K-BLDG., 3, SANGAM-RO 41GIL,  
GANGDONG-GU, SEOUL 05307, KOREA

PHONE : 02 479 2703  
FAX : 02 479 2705  
e-mail : taekwang@tkec.co.kr  
Website: www.tkec.co.kr



Valeport's Hyperion Fluorometer sensor range, when combined with SWiFT, delivers high performance measurements of Phycocyanin in a compact & robust package.

### Sensor Specification

#### Phycocyanin\*

<b>Excitation</b>	590 nm
<b>Detection</b>	650 nm
<b>Dynamic Range</b>	0-9,000 ppb 2 gain settings: 0-50, 0-9,000 software controlled

<b>Minimum Detection</b> (3x SD in RO water)	<0.08 ppb
---	-----------

<b>Linearity</b>	0.99 R <sup>2</sup>
------------------	---------------------

<b>Response Time</b>	0.03 to 2 sec
----------------------	---------------

<b>Output Rate</b>	0.5 Hz to 32 Hz (free running) software controlled
--------------------	---

#### Conductivity#

<b>Range</b>	0 - 80 mS/cm
--------------	--------------

<b>Resolution</b>	0.001 mS/cm
-------------------	-------------

<b>Accuracy</b>	±0.05 mS/cm
-----------------	-------------

#### Temperature (Platinum Resistance Thermometer)

<b>Range</b>	-5°C – +35°C
--------------	--------------

<b>Resolution</b>	0.001°C
-------------------	---------

<b>Accuracy</b>	±0.01°C
-----------------	---------

#### Pressure (Temperature compensated piezo-resistive pressure transducer)

<b>Range</b>	50 Bar
--------------	--------

<b>Resolution</b>	0.001% FS
-------------------	-----------

<b>Accuracy</b>	±0.01% FS
-----------------	-----------

#### Sound Velocity (Digital time of flight sensor)

<b>Range</b>	1375 – 1900 m/s
--------------	-----------------

<b>Resolution</b>	0.001 m/s
-------------------	-----------

<b>Accuracy</b>	±0.02 m/s
-----------------	-----------

#### Salinity#

<b>Range</b>	0 - 42 PSU
--------------	------------

<b>Resolution</b>	0.001 PSU
-------------------	-----------

<b>Accuracy</b>	±0.05 PSU
-----------------	-----------

#### Density

<b>Range</b>	990 - 1035 kg/m <sup>3</sup>
--------------	------------------------------

<b>Resolution</b>	0.001 kg/m <sup>3</sup>
-------------------	-------------------------

<b>Accuracy</b>	±0.05 kg/m <sup>3</sup>
-----------------	-------------------------

\*Calibrated against Phycocyanin in water/Phosphate buffer solution.

#Calculated Accuracies. Calculations based on Valeport's proprietary DASH formula.

### Physical dimensions

<b>Materials</b>	Housing: Titanium
------------------	-------------------

Sinker weight: Stainless steel

Optical window: Sapphire glass

<b>Depth rating</b>	500m
---------------------	------

<b>Dimensions</b>	Ø78mm x Length 307mm (with sinker weight)
-------------------	---

<b>Weight</b>	2.7kg (in air) / 1.7kg (in water) including optional sinker weight
---------------	--

### Communications (set-up and data offload)

Bluetooth v4 - low energy

USB Serial

### Electrical

<b>Battery</b>	Internal rechargeable Li-ion battery pack
----------------	---

<b>Charging</b>	USB - Supplied mains AC adapter
-----------------	---------------------------------

### Software

- Connect iOS for Bluetooth compatible mobile devices:
  - instrument set-up, data offload and data display
- Connect PC for both USB and Bluetooth connectivity:
  - instrument set-up, data offload and data display
- Both will export data in common file formats that are compatible with industry standard Hydrographic software packages
- Android App to follow

### Ordering

<b>0660047-50-FP</b>	SWiFTplus profiler with Phycocyanin sensor 500m rated
----------------------	---

- Supplied with:
- Deployment weight
  - PC Bluetooth adapter
  - USB interface and charging cable and charger
  - Valeport Connect PC software \ iOS App
  - Transit Case



### Datasheet Reference: Phycocyanin | April 2020

As part of our policy of continuing development, Valeport Ltd. reserve the right to alter at any time, without notice, all prices, specifications, designs and conditions of sale of all equipment - Valeport Ltd © 2020

