



SeaWATCH

ADCP

Self-Contained

300 kHz / 600 kHz / 1200 kHz

The Rowe Technologies **SeaWATCH** product family is the most versatile self-contained Acoustic Doppler Current Profilers (ADCPs) and represent the industry state-of-the-art in acoustic Doppler technology. The compact form factor, powerful electronics and robust signal processing, provide a versatile platform capable of producing precise current profile measurements over extended ranges.

The product comes in three different frequencies; 300 kHz, 600 kHz, and 1200 kHz, and is available in different depth package options – 300 m, 3000 m, and 6000 m.

Each unit in the product family leverages a core, common set of electronics in a flexible form factor. This, combined with multiple packaging options, provides a cost-effective and extremely capable instrument to address a wide variety of oceanographic applications, from shallow water to full-ocean depth.

The **SeaWATCH** ADCP's are well suited for a variety of coastal and offshore oceanographic applications including meteorological and wave data acquisition, environmental management, coastal engineering site assessment, and oil/gas exploration and drilling. Rowe systems are easily deployed on buoys, moorings, or sea-floor structures.



SeaWATCH Specifications

Single Frequency (nominal):	300kHz	600kHz	600kHz	1200kHz
Piston Ceramic Size:	3 in	3 in	2 in	2 in
Beam widths (2 way):	2.70°	2.00°	2.00°	1.01°
Beam Spacing:			4 beams inclined 20°	
Velocity Range:		+/- 20 m/s Max; +/- 5 m/s Typical		
Resolution:	0.01 cm/s			
Number of Cells:	up to 200			
Cell Size:		2.0 cm minimum		
Current Profiling:				
Maximum Range:				
Narrow Band:	150 m	75 m	70 m	30 m
Broad Band:	100 m	50 m	45 m	20 m
Long-Term Accuracy (High Accuracy Option):	± 0.70%, ± 2mm/s	± 0.25%, ± 2mm/s	± 0.50%, ± 2mm/s	± 0.25%, ± 2mm/s
Long-Term Accuracy (Low Accuracy Option):			+/-1.0%, +/- 2 mm/s	
BB Single-Ping Precision:	3.5 cm/s @ 4 m cell depth	3.5 cm/s @ 2 m cell depth	3.5 cm/s @ 1 m cell depth	
NB Single-Ping Precision:	20 cm/s @ 4 m cell depth	20 cm/s @ 2 m cell depth	20 cm/s @ 1 m cell depth	
Data Output Rate:		1-2 Hz typical; 10 Hz max		
Bottom Tracking:				
Maximum Range:	300 m	130 m	120 m	50 m
Maximum Bottom Track Speed:			15 m/s	
Long-Term Accuracy (High Accuracy):	± 0.70%, ± 2 mm/s	± 0.25%, ± 2 mm/s	± 0.50%, ± 2 mm/s	± 0.25%, ± 2 mm/s
Long-Term Accuracy (Low Accuracy):		+/-1.0%, +/- 2 mm/s		
Single-Ping Precision:	± 0.6 cm/sec @ 3 m/sec	± 0.5 cm/sec @ 3 m/sec	± 0.4 cm/sec @ 3 m/sec	± 0.4 cm/sec @ 3 m/sec
Resolution:				
Sensors:				
Compass: Range/Accuracy/Resolution:	0-360° / 1% RMS / 0.01°			
Pitch/Roll: Range/Accuracy/Resolution:	Roll +/- 180° / Pitch +/- 90° <1% RMS / 0.01°			
Water Temp: Range/Accuracy/Resolution:	-5° - 70° C / +/- 0.15°C			
Pressure: Range/Accuracy:	Selectable / +/- 0.1% Range			
Materials Options:				
Input Power:				
Voltage Range (Ext DC Input):	12 - 36 VDC			
Average Power (5% duty cycle) / Peak Current:	23 W typical	30 W typical	30 W typical	23 W typical
Output Data:				
Communications:	RS-485, RS232, 100Base T/Ethernet (self-contained only)			
Internal Recording:	32 GByte			
Environmental:				
Temperature:	-5° to 45° C (Operating), -30°C to 60° C (Storage)			
Depth Rating:	50m, 300 m, 3000 m, and 6000m (600 kHz)			

** In Development
 Specifications may be subject to change at any time in the future.

Product Features:

- Multi-Use Configuration - 3-Axis Current Profile and Bottom Track or Water Track Velocity Measurements.
- User-Programmable Acoustic Transmission - Broad Band, Narrow Band, and Pulse-to-Pulse Coherent Technologies.
- User-Selectable Signal Processing Options Optimize Acquisition Parameters for Precise, High-Accuracy Measurements.
- Temperature Sensor and Flux Gate Compass with Pitch and Roll Sensor.
- ROWE's Windows™-Based Pulse Software Included For Data Acquisition, Display and Export.

Product Options:

- External Battery Pressure Housing Options Allow for Extended Deployments.
- Optional Pressure Sensor.

