



# SWiFT SVPplus Turbidity

## Multi-parameter profiler

Valeport's SWiFT SVPplus Multi-Parameter Profiler with a Turbidity sensor combines survey-grade sound speed, temperature and pressure sensor technology with Turbidity observations. The package is completed with the convenience of **Bluetooth®** wireless technology, rechargeable battery and an integral GNSS module to geo-locate each profile.

- Multi-Parameter Profiler
  - CTD, Sound Speed, Salinity, Density
  - Up to 32Hz sampling rate
  - Dual Optical Backscatter (OBS) and Nephelometer Turbidity Sensor
- Bluetooth and USB connectivity
- Integral GNSS receiver for geo-location of profile and time synchronisation
- Rechargeable Lithium-ion Battery
- Dedicated PC software and iOS or Android App

Valeport's Turbidity technology is essentially two sensors in one. The first is a "classic" nephelometer, using a 90° beam angle for turbidity levels between 0 and 2,000 NTU. The second sensor uses Optical Backscatter (OBS) for turbidity levels up to 10,000 NTU. The sensors output data separately and simultaneously at a programmable rate. This means that there is no need to switch ranges as conditions vary. Intelligent sampling and the use of a 24 bit ADC eliminates the need to switch gain.

## DATA SHEET

### Product Details



MULTI-PARAMETER  
CTD



SOUND  
SPEED



OPTICAL



OCEAN & CONNECT  
PATHWAY EDITION  
SOFTWARE



USB



Rechargeable  
Battery



GNSS

## Sensor Specification

Turbidity	
Linear Range	Nephelometer: 0 to >1,000 NTU - linear response <sup>1</sup> OBS: 0 to >4,000 NTU - linear response <sup>1&amp;2</sup> <sup>1</sup> depending on suspended material <sup>2</sup> >4,000 NTU has a non-linear monotonic response that allows derivation of higher values using look-up tables\secondary calibration
Linearity	0.99 R <sup>2</sup>
Minimum Detection Level	0.03 NTU (Nephelometer)

Conductivity#	
Range	0 - 80 mS/cm
Resolution	0.001 mS/cm
Accuracy	±0.05 mS/cm

Temperature (Platinum Resistance Thermometer)	
Range	-5°C – +35°C
Resolution	0.001°C
Accuracy	±0.01°C

Pressure (Temperature compensated piezo-resistive pressure transducer)	
Range	50 Bar
Resolution	0.001% FS
Accuracy	±0.01% FS

Sound Velocity (Digital time of flight sensor)	
Range	1375 – 1900 m/s
Resolution	0.001 m/s
Accuracy	±0.02 m/s

Salinity#	
Range	0 - 42 PSU
Resolution	0.001 PSU
Accuracy	±0.05 PSU

Density	
Range	990 - 1035 kg/m <sup>3</sup>
Resolution	0.001 kg/m <sup>3</sup>
Accuracy	±0.05 kg/m <sup>3</sup>

#Calculated Accuracies. Calculations based on Valeport’s proprietary DASH formula.

## Physical dimensions

Materials	Housing: Titanium
	Sinker weight: Stainless steel
	Optical window: Sapphire glass
Depth rating	500 m
Dimensions	Ø78 mm x Length 307 mm (with sinker weight)
Weight	2.7kg (in air) / 1.7kg (in water) including optional sinker weight

## Communications (set-up and data offload)

USB Serial	
Bluetooth v4	Low energy

Electrical	
Battery	SWiFT Battery endurance depends on the sampling scenario used – contact Valeport for more information.  100 days endurance 2 profiles per day to 100 m* 42 days - 3 profiles a day to 500 m* 2 days continuous running (normal power mode)  (*Utilising Bluetooth Sleep mode)
Charging	USB - Supplied mains AC adapter

Software	
iOS and Android Valeport Connect Pathway Edition for Bluetooth compatible mobile devices – instrument set up, data offload, display and translation to common data formats. Valeport’s Ocean PC software, with both USB cable and Bluetooth connectivity, for instrument setup, data extraction, display and translation to common data formats.	
Instrument and data time is synchronised to GNSS, UTC.	

## Ordering

0660047-50-TU	SWiFT SVPplus profiler with Turbidity sensor 500 m rated
Supplied with	PC Bluetooth adapter USB interface and charging cable 1.5 A charger Valeport Ocean software Operating manual System transit case



The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Valeport Ltd is under license. Other trademarks and trade names are those of their respective owners.

### Datasheet Reference: SWiFT SVPplus Turbidity | April 2024

As part of our policy of continuing development, Valeport Ltd. reserve the right to alter at any time, without notice, all prices, specifications, designs and conditions of sale of all equipment - Valeport Ltd © 2024

